Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

	, , ,		
or trade mark:	UMAGE		
ess: UMAGE ApS	, Havnegade 29, 105	58 Copenhagen, DK	
r: 2408 (light-sou	ırce)		
urce:			
ogy used:	LED	Non-directional or directional:	NDLS
• •	Custom LED PCB		
c interface)	24V DC 380MA		
ains:	NMLS	Connected light source (CLS):	No
light source:	No	Envelope:	-
light source:	No		
l:	No	Dimmable:	No
	Product para	meters	1
	Value	Parameter	Value
	General product p	arameters:	
00 h), rounded st integer	10 1 270 in	Energy efficiency class Correlated colour	3 100
60º), in a wide n a narrow cone	Sphere (360°)	temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	
oower (P _{on}),	9,2	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
ssed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83
Height	139	Spectral power distribution in the	See image in last page
	r: 2408 (light-souurce: logy used: b-type c interface) lains: light source: light source: d: mption in on- 00 h), rounded st integer us flux (фuse), efers to the flux 60°), in a wide n a narrow cone	r: 2408 (light-source) urce: logy used: Custom LED PCB 24V DC 380mA NMLS light source: No light source: No Product paral Value General product p mption in on- 00 h), rounded st integer us flux (фuse), effers to the flux 60°), in a wide n a narrow cone nower (Pon), 9,2 dby power (Pnet) seed in W and	r: 2408 (light-source) urce: logy used: LED Non-directional or directional: D-type Custom LED PCB 24V DC 380mA lains: NMLS Connected light source (CLS): e light source: No Envelope: light source: No Dimmable: Product parameters Value Parameters Walue Parameters Mono Dimmable: Product parameters Inption in on- O0 h), rounded st integer us flux (фuse), efers to the flux 60°), in a wide in a narrow cone in a narrow cone Dower (Pon), 9,2 Standby power (Psb), expressed in W and rounded to the nearest 100 K, that can be set Odby power (Pnet) Seed in W and second decimal dby power (Pnet) seed in W and second decimal Description in W and second decimal Description in On- O0 h), rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set Dower (Pon), 9,2 Standby power (Psb), expressed in W and rounded to the second decimal Description in W and second decimal Description in On- O0 h), rounded to the nearest integer, or the range of CRI-

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity	0,435	
		coordinates (x and y)	0,396	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	9	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

